

ENDURA S10i 1-10x24i SFP

Features

- Wide angle optical system with wide and flat field of view, even at low magnification
- Expansive 10x zoom erector configuration with versatile 1-10 magnification range
- Robust 30mm tube design of single piece construction
- Fully multi coated lenses (Low Dispersion)
- P22i Illuminated Red Dot Reticle with MRAD based stadia and 0.2MRAD holds
- Daytime Bright
- Glass Etched (fine) not fiber construction
- 12 illumination settings with an "off" between each step
- 30.0MRAD elevation travel range with 0.1MRAD adjustment per click
- Push/Pull locking turret caps
- Includes a throw lever for magnification ring
- Includes sunshade and flip up covers
- Nitrogen Purged, waterproof, fogproof, shockproof
- Each unit is hand tested in the United Kingdom before sale

Warranty

- Repair or Replace if the scope doesn't perform. **No charge. No time limit.**

MAGNIFICATION RANGE	1-10x
FIELD OF VIEW @ 100M	38.4m-3.84m (125'11"-12'7")
EYE RELIEF	89mm - 91mm
MAX ELEVATION ADJUSTMENT RANGE	30.0MRAD
MAX WINDAGE ADJUSTMENT RANGE	30.0MRAD
ADJUSTMENT VALUE PER CLICK	0.1MRAD
ADJUSTMENT PER TURN	10.0MRAD
FIXED PARALLAX DISTANCE	25M (S1001) or 100M (S1002)
RETICLE CHOICES	P22i (MRAD)
RETICLE INSTALL	Second Focal
TOTAL LENGTH	275mm
WEIGHT	525g
TUBE DIAMETER	30mm
CONSTRUCTION	1 Piece Tube/Saddle
OBJECTIVE LENS DIAMETER	24mm
OUTER OBJECTIVE DIAMETER	30mm
OUTER OCULAR DIAMETER	44.5mm
ADDITIONAL SUNSHADES	1 Supplied
FLIP UP LENS COVERS	Yes, Supplied
CONFIGURATIONS AND ORDER CODES	S1001 (25m) or S1002 (100m)

